

TILE GROUTS

UNIGROUT 201

PRODUCT DESCRIPTION

Unigrout 201 is a cement-based, polymer-modified tile grout mortar, for filling grout joints of ceramic wall and floor tile, porcelain tile, and mosaic tile, for walls and floors

CHARACTERISTICS

Smooth texture. For indoor and outdoor use.
 Non - cracking. Easy to apply.
 Easy to clean. Rapid hardening.
 Economical. Weather resistant.
 Temperature resistance from +70oC to -20oC

APPLICATION

Unigrout 201 is applied internally and externally and where heavy traffic is present. Unigrout 201 is ideal for bathrooms, shower rooms, kitchens, in private and public buildings and in swimming pools.

STANDARDS

Unigrout 201 complies with ANSI 118.6 standards.

PACKING

5 kg 1 Bag
 10 kg 1 Bag

COMPOSITION

Unigrout 201 is a premix of finely selected raw materials, comprising clean, very fine silica sand, portland cement, and selected additives to enhance workability and application characteristics. Unigrout 201 is available in a variety of attractive colors.

Colors are formulated with high quality inorganic pigments providing high chemical and UV stability.

TECHNICAL SPECIFICATIONS

Powder Intensity: Approximately 1.2 kg/l
Color: Grey, white or can you name standard color range
Mix Proportions: 3 liters of water for 10 kg bag of UNI GROUT 201
Pot Period: Approximately 1 hour



GROUT COVERAGE

Approximate Grout Coverage, M² Per KG of Grout

Tile Dimensions (cm x cm x mm)	Joint Width mm	
	1.5 mm	3 mm
10 x 10 x 9	4.0	2.0
20 x 20 x 9	6.3	3.2
30 x 20 x 9	8.3	4.2
35 x 25 x 9	9.3	4.7
49 x 30 x 9	12.5	6.3
35 x 50 x 9	15.0	7.5

LOCATION

